



Suitable for external uses.



The product can be pigmented.

CALCE BAROCCO

LIME BAROCCO

Description of product

"Grassello Paste" with selected white marble powders and hydraulic binders for a prestigious grooved, imitation wood or fancy finishing.

Application Field

Prestigious decorations, medium thickness, matt finishing for interiors and exteriors.

Product characteristics

CALCE BAROCCO interior and exterior finishing which permits to obtain, with one coat, original decorative finishing in relief. The accurate composition of the product permits a vast range of application methods which create many fancy finishing. The colour shades can be personalized by using the colour scheme of the Tinctometric system Luxur&Lime. The tradition of lime, produced with an advance technology, aims Bericalce towards the Environment Care and Green Division market. The natural raw materials, accurately selected, give CALCE BAROCCO a very high ecologic value: the dispersion of humidity avoids the growth of moulds and bacteriums, without using chemical additives. Non-flammable and low odour.

Technical data	
Name	Calce Barocco
Composition	"Dolomitic" Lime Putty (Grassello) minimum 12 month aged, marble powders and additives for less than 4%
Aspect	Dense paste
Color	Natural White
Dilution	Ready to use (if needed a dilution in water 0-5%)
Quantity per layer	approx. 1,2 - 1,6 m ² /kg
PH	13 in aqueous solution
Vapour permeability	SD - 0,05m (DIN 52615)
Water absorption	w - 0,4kg / (m ² h0,5) (EN1062-3:2001)
VOC class	VOC 0g/l - wall paint and subcategory "L" max.value UE2010 30g/l
Specific weight	1,70 kg/l
Packaging	25 kg buckets
Storage	Keep in dry place with temperture min.5° - 30°C max.
Notice	Protect the surfaces from rain in the first 24 - 48 hours after application

CALCE BAROCCO

Instructions for use

- Prepare the base with a specific Primer, Acrylic Insulator or levelling base like Insulating Anchor Primer Berico.
 - Application with stainless steel / plastic trowel, decoating tools
 - Base must be clean and dry, any unsubstantial parts, traces of oil or grease must be removed; plaster any irregularity of the base.
 - Application of 1 or more coatings.
 - After spreading one layer, proceed with the trowel and tools to create the first decorating effects
 - When the product is touch dry, proceed with more movements with the trowel in order to refine the decoration desired
 - When drying is complete, the surface must be made smooth and uniform.
 - To further enhance the product, decorative veilings can be done
 - It's important that the product be of the correct consistence and dilution according to the temperature and absorption of the surface. In exteriors the product is guaranteed only if apply on a base of Classic Intonachino
 - Temperature of application: 5° to 35°C
 - All lime-based products have a normal drying time according to the thickness but, the real hardness is obtained through carbonation which occurs on contact with the air.
- This process could last many months

Notes

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsibility regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

Date of issue 01.04.2004

Revision nr.1 05.06.2018

BeriCalce ITALIA

Via Odorico da Pordenone, 18

36100 Vicenza - ITALY

Phone (+39) 0444 929102

Fax (+39) 0444 929102

Skype: bericalce

info@bericalce.com

bericalce.com