

TECHNICAL CHART 37

PEARLESCENT WAX

Description of product

Decorative wax with a pearlescent effect, based on natural beeswax, which serves as decoration and protection for all types of supports.

Application Field

Decoration, protection and conservation for prestigious decorative finishing.

Product characteristics

PEARLESCENT WAX is an innovative product that gives, when applied to surfaces, a fine metallic-pearlescent effect, its delicate appearance, gives a youthful touch and an elegant highlight in every type of ambience. Excellent on "Marmorino Matt 600", lends itself to be applied optimally over the entire range of decorative products of the Luxury&Lime line.

PEARLESCENT WAX protects the substrate from stains and facilitates maintenance. Its application makes more solid the surface where applied, penetrating into the pores giving greater resistance, the treated walls remain stable over time without discoloration.

PEARLESCENT WAX is a very natural product made from beeswax, it's used to make bright, pearlescent interior effects on walls covered with stucco and antique Venetian plaster. Its composition is a synthesis of natural bee wax, pearlescent

Technical data	
Name	Pearlescent Wax
Composition	Bee wax, pure Marsiglia soap, pearlescent pigments and special additives
Aspect	Dense liquid
Color	Neutral, Light Gold, Light Silver, Light Bronze, Light Green, Light Blue, Light Red
Dilution	Ready to use
Quantity per layer	approx. 7 - 10 m2/kg
PH	8 - 10
Solid contents	approx. 13%
Viscosity	8.000 – 10.000 (Brookfield R.P.M. 20, S 04, T 25° C)
VOC class	VOC 0g/l - wall paint and subcategory "L" max.value UE2010 30g/l
Specific weight	0,96 kg/litre
Packaging	1 - 2,5 - 5 Lt packaging
Storage	Keep in dry place with temperature min.5° - 30°C max.
Notice	Protect the surfaces during the 12 hours after application

PEARLESCENT WAX

Instructions for use

- Application with sponge, pads, cloths and paintbrush
- Application of 1 or more coats according to needs
- PEARL WAX is ready to use, stir with care
- Let surface dry for at least 24 hours before application
- Spread the wax using a sponge and proceed of about 1 sq. mt per time, insisting with spreading until the surface does no longer absorb. Remove the excess of wax from surface
- The product can be applied using different tools: sponge, pad, cloth, paintbrush according to the decorative effect to obtain. Remove with cloth any excess of wax
- After about 30 min. and not more than 2 hours, proceed to polishing with special cloths or using a polishing machine with wool pads
- Protect from rain external decoratives for at least 48 hours
- The product maintains its characteristics for about 12 months if protected from excessive heat or coldness
- Temperature of application 5° - 35°C

Notes

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsibility regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

Date of issue 01.04.2019

BeriCalce ITALIA

Via Odorico da Pordenone, 18

36100 Vicenza - ITALY

Phone (+39) 0444 929102

Fax (+39) 0444 929102

Skype: bericalce

info@bericalce.com

bericalce.com