



Suitable for external uses.



The product can be pigmented.

TECHNICAL **CHART 103**

MEGAPRIMER UNIFORMANTE

Description of product

Anchoring primer based on acrylic copolymers in aqueous phase, with high insulating power. It guarantees excellent coverage, permeation and adhesion on any substrate, and also reduces the risk of salt efflorescence formation.

Application Field

For interiors and exteriors.

Product characteristics

MEGAPRIMER UNIFORMANTE is an anchoring primer with high insulating power, capable of guaranteeing excellent coverage.

It is particularly suitable for low absorbent substrates, old paints, concrete, chipboard panels.

Its final appearance is white in color.

Technical data	
Name	Megaprimer Uniformante
Composition	Mixed acrylic resins, titanium dioxide and additives.
Aspect	Semidense Paste
Color	White
Dilution	In water 50 - 60%
Quantity per layer	approx. 10 - 11 m ² /kg
PH	9,5
VOC class	VOC 7 g/l - wall paint and subcategory "L" max.value UE2010 30g/l
Specific weight	1,33 Kg/l
Packaging	15 -5 - 2,5 - 1 Lt packaging
Storage	Keep in dry place with temperture min.5° - 30°C max.
Notice	Protect the surfaces during the 12 hours after application

MEGAPRIMER UNIFORMANTE

Instructions for use

- Prepare the surface: Old paintings must be well stick, clean and dry.
- Any unsubstantial parts must be removed, eliminate traces of oil or grease, level any irregularity of the base consolidate and plaster any cracks or holes.
- MEGAPRIMER UNIFORMANTE must be diluted in water and carefully stirred.
- Apply 1 or more coats according to needs. For surfaces particularly porous apply a concentrated layer
- Protect from rain.
- Verify that the product be completely consolidated and that it has fulfilled its function.
- Temperature of application 10° - 35°C
- Do not apply on wet or metal surfaces.

Notes

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsibility regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

Date of issue 20.07.2020

BeriCalce ITALIA

Via Odorico da Pordenone, 18

36100 Vicenza - ITALY

Phone (+39) 0444 929102

Fax (+39) 0444 929102

Skype: bericalce

info@bericalce.com

bericalce.com