



### TECHNICAL CHART 66

# **STUCCO RASANTE**

### **Description of product**

Skim coat composed of extremely fine marble powders, special resins, oils and natural essences.

### **Application Field**

Synthetic skim coat for interiors, excellent as a base for decorations, for very fine smoothing.

### **Product characteristics**

STUCCO RASANTE is a synthetic leveling, filling skim coat with excellent thickening power. Its special blend makes it more workable than other similar products. STUCCO RASANTE is very smooth, fine and consistent, and guarantees a high level of spreadability. The product is ready to use, but can be diluted with water if necessary. It is a product that guarantees good breathability to the walls where it is applied, thanks to its careful composition.

	Technical data
Name	Stucco Rasante
Composition	Special resins mixed with marble powders and precious oils
Aspect	Dense paste
Color	Natural white
Diluition	Ready to use (0÷5% in water)
Quantity per layer	approx. 0,5 - 1 m²/Kg
PH	approx. 7,5-8
Vapour permeability	SD ~ 0,04 m (DIN 52 615)
Water absorption	w ~ 0,3 Kg / (m <sup>2</sup> h0,5) (EN 1062-3:2001)
VOC class	VOC 30 g/l, wall paint and subcategory "L" max.value UE 2010 30g/l
Specific weight	1,65 Kg/lt
Packaging	5 - 15 Lt. packages
Storage	Keep in dry place with temperature 5°÷30°C
Notice	Protect surfaces during the 12 hours after application

## TECHNICAL CHART 66 STUCCO RASANTE

### Instructions for use

- Application with stainless steel trowel.
- The product is ready to use, mix carefully before use.
- Make sure the surface is clean and dry.
- We recommend the bottom leveling type MICRO-PRIMER VENEZIANO of Bericalce.
- Temperature of application 5°÷35°C

### Notes

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsability regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

### Date of issue 01.02.2017

#### BeriCalce S.r.l.

Via Odorico da Pordenone, 18 36100 Vicenza - ITALIA Tel./Fax (+39) 0444 929102 Tel. (+39) 0444 654919 Skype: bericalce info@bericalce.com



Page 2of2