



## **SAFETY DATA SHEET 120**

# **RASOCOCCIO**

### 1 IDENTIFICATION OF THE MIXTURE AND THE COMPANY

1.1 Product identifier

Product name RASOCOCCIO

1.2 Relevant identified uses of the substance or mixture and uses advised against

Description/Application LEVELLING STUCCO IN POWDER

1.3 Details of the supplier of the safety data sheet

Name: BERICALCE S.R.L.

Full address: Via Piave n.23 - 36033 Isola Vicentina (VI) - Italia

Phone: +39 0444 929102 +39 0444 654919

Fax: +39 0444 929102

E-mail address of the competent person

responsible to the Safety Data Sheet info@bericalce.com

1.4 Emergency telephone number

For urgent inquiries refer to SANITARY EMERGENCY

#### 2. HAZARD IDENTIFICATION

#### 2.1 Classification of the substance or mixture

The product is classified as hazardous according to the provisions of Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adaptationxs. The product thus requires a safey data sheet complies with the provisions of Regulation (EC) n. 1907/2006 and subsequent amendments. Furtherinformation on the risks to health and/or the environment are given in sec. 11 and 12 of this sheet.

Hazard classification and indication:

Serious eye damage, category 1 H318 It causes serious eye damage. Skin irritation, category 2 H315 It causes skin irritation.

Specific toxicity for target organs

- single exposure, category 3 H335 It may cause respiratory irritation. Skin sensitization, category 1 H317 It may cause allergic skin reaction.

#### 2.2 Label elements

Danger labeling under Regulation (EC) 1272/2008 (CLP) and subsequent amendments.





Warnings:

Danger:

Hazard:

H318 It causes serious eye damage. H315 It causes skin irritation.

H335 It may cause respiratory itrritation.
H317 It may cause an allergic skin reaction.

Safety advice:

P264 To wash hands thoroughly with soap and water after use.

P272 Contaminated work clothing should not be allowed out of workplace.

P280 Wear protective gloves and protect eyes / face.

P304+P340 IF INHALED: move the victim to fresh air and keep at rest in a position comfortable

for breathing.

P310 Immediately call a POISION CENTER or get medical advice/attention.

P403+P233 Keep container tightly closed and in a well-ventilated place..

It contains: Hydrated lime

Concrete Portland Cr(VI) < 2 ppm

### 2.3 Other dangers

Based on available data, the product does not contain any PBT or vPvB substances as more than 0,1%

#### 3 COMPOSITION / INFORMATION ON INGREDIENTS

#### 3.1 Substance

No relevant information.

### 3.2 Miscele

It contains:

Identification Conc. %. Classification 67/548/CEE. Classification 1272/2008 (CLP).

**CALCIUM CARBONATE** 

CAS. 471-34-1  $30 \le x < 35$  Substance with a community exposure limit in the workplace

CE. 207-439-9 INDEX. -CEMENT

CAS. 65997-15-1 20 ≤ x < 25 Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1 H317

CE. 266-043-4

INDEX. -

**HYDRATE LIME** 

CAS.1305-62-0 13 ≤ x < 17 Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335

CE. 215-137-3

INDEX. -

#### COPOLYMER OF VINYL ACETATE AND ETHYLENE WITH CHARGE AND PROTECTOR COLLOID

CAS. -  $5 \le x < 6.5$  Substance with a community exposure limit in the workplace

CE. -INDEX. -

The full text of hazard (H) is specified in section 16 of the sheet.

#### 4 FIRST AID MEASURES

### 4.1 Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

Page 2of10 Bericalce

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention. INGESTION: Have the subject drink as much water as possible. Get medical advice/attention.

Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take precautions for rescue workers.

### 4.2 Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

### 4.3 Indication of any immediate medical attention and special treatment needed.

Follow doctor's instructions.

#### 5 FIREFIGHTING MEASURES

### 5.1 Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be conventional: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use water.

#### 5.2 Special hazards arising from the substance or mixture

HAZARDS CAUSED BYEXPOSURE IN THE EVENTOF FIRE

Do not breathe combustion products.

### 5.3 Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the cointainers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contamined water used for extinction and the remains of the fire according to applicable regulations.

**EOUIPMENT** 

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### 6 ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing dust and provide adequate ventilation or wear a protectivr mask or an adequate protective equipment (see section 8).

Wear suitable protective equipment (including personal protective equipment referred to in section 8 of the safety datas sheet) to prevent any contmination of skin, eyes and personal clothing. These direction are valid both for the workers to work which for emergency interventions.

### 6.2 Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3 Methods and material for containment and cleaning up

Use dry cleanup methods such as vacuum cleaners or vacuum extraction (greased portable industrial, equipped with high efficiency particulate filters or equivalent techniques) that do not scatter dust in the environment. Never use compressed air. Ensure that workers wear appropriate personal protective equipment (see section 8) in order to prevent inhalation of dust and contact with skin and eyes. Deposit spillage in containers for future use. Verify the compatibility of containers' material in section 7. Ensure adequate ventilation of the place affected by the loss. The disposal of contaminated material must be made in accordance with section 13.

#### 6.4 Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

Page 3of10 Bericalce

#### 7 HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Handle the product after consultation with all other sections of the sheet. Store in sealed and labeled containers. Avoid dispersal into the environment. Avoid contact with eyes and skin and exposure to concentrations of dust holes. Avoid the development and deposition of dust. Use a localized ventilation system. Do not eat, nor drink, nor smoke while handling it. Remove contaminated clothing and equipment before entering eat areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3 Specific end use(s)

Information not available.

#### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

EU OEL EU Direttiva 2009/161/UE; Direttiva 2006/15/CE; Direttiva 2004/37/CE;

Direttiva 2000/39/CE.

TLV-ACGIH ACGIH 2016

**CALCIUM CARBONATE** 

Threshold limit value								
Туре	State	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm			
TLV-ACGIH		10		J		inhalab.		
TLV-ACGIH		3				respir.		

CEMENT

Threshold limit value								
Туре	State	TWA/8h ma/m3	maa	STEL/15min ma/m3	ppm			
TLV-ACGIH		1	1- 1-	<i>J.</i>	1- 1-			

HYDRATED LIME

Threshold limit	t value						
Туре	State	TWA/8h		STEL/15min			
		mg/m3	ppm	mg/m3	ppm		
OEL	EU	1		4		respir.	
Expected conce	ntration of	no effect on the	e environ	ment - PNEC.			
Reference value in fresh water				490		mg/l	
Reference value	for the terr	estrial comparti	ment	1080		mg/l	

COPOLYMER OF VINYL ACETATE AND ETHYLENE WITH CHARGE AND PROTECTOR COLLOID

Threshold limit value									
Туре	State	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm				
TLV-ACGIH		10				respir			
TLV-ACGIH		3				torac.			

Legend:

(C) = CEILING; INHALAB = inhalable fraction; RESPIR = Respirable fraction; TORAC = Thoracic fraction.

VND = identified hazard but no DNEL/PNEC available; NEA = no expected exposure;

NPI = no hazard identified.

### 8.2 Exposure controls

As the use if adequate technical equipment must always take priority over personal protection equipment must always take priority over personal protection equipment, ensure good ventilation in the workplace through effective local aspiration. For the selection of personal protective equipment, if necessary, request advice from your chemical substance suppliers.

The personal protective equipment must bear the CE marking attesting to their compliance with applicable regulations. Provide emergency shower with a pan for face and eyes.

Page 4of10 Bericalce

#### HAND PROTECTION

Protect your hands with work gloves, category III (ref. law EN 374). Final selection of the material of the gloves must be considered: compatibility, degradation, breakage times and permeation. In the case of preparations the resistance of protective gloves to chemicals should be checked before use, as it expected. The gloves' limit depends on the duration and method of use.

#### SKIN PROTECTION

Wear work clothes with long sleeves and safety footware for professional use category II (ref. Directive 89/686/ EEC and law EN ISO 20344). Wash with soap and water after removing protective clothing.

#### **FYF PROTECTION**

We reccomend wearing hood visor or protective visor together with airtight goggles (ref. law EN 166). RESPIRATORY PROTECTION

We recommend the use of a P-type filtering face mask (ref. law EN149), or equivalent device, the class (1, 2 or 3) and actual need will be defined depending on the outcome of the risk assessment.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Powder

#### PHYSICAL AND CHEMICAL PROPERTIES 9.

#### 9.1 Information on basic physical and chemical properties

Appearance Colour Light rose Odour Odorless Odour threshold Not available Not available Hq Melting point / freezing point Not available Initial boiling point Not available Boiling range Not available Flash point Not infiammable Not available Evaporation rate Flammability (solid, gas) Not infiammable Lower inflammability limit Not infiammable Not infiammable Upper infiammability limit Lower explosive limit Not available Not explosive Upper explosive limit Not available Vapour pressure Vapour density Not available Relative density Not available Not available Solubility Partition coefficient:: n-octanol/water Not available Not infiammable Auto-ignition temperature Not available Decomposition temperature Not available Viscosity Explosive properties Not explosive Oxidising properties Not available

#### 9.2 Other information not available

#### 10 STABILITY AND REACTIVITY

### 10.1 Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

When mixed with water, it hardens forming a stable mass that does not react with the environment.

#### 10.2 Chemical stability

The product is stable in normal conditions of use and storage.

It must be kept dry. It should be avoided contact with incompatible materials.

The wet cement is alkaline and incompatible with acids, with ammonium salts, with aluminum and other non-noble metals. Cement in contact with the hydrofluoric acid decomposes producing corrosive silicon tetrafluoride gas. Cement reacts with the water and forms silicates and calcium hydroxide.

Silicates in cement react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride and oxygen difluoride.

The package integrity and compliance with the conservation mode mentioned in section 7.2 are able to conserve the quality.

### 10.3 Possibility of hazardous reactions

INo hazardous reactions are foreseeable in normal conditions of use and storage.

Cement decomposes with hydrofluoric acid with formation of H2SIF6 (silicon tetrafluoride), which is corrosive. Cement reacts with water to form silicates and calcium hydroxide. Silicates in cement react with powerful oxidizers such as fluorine, boron trifluoride, manganese trifluoride and oxygen difluoride.

Hydrated lime reacts esothermically with acids. If heated to more than 580°C, calcium dihydroxide decomposes to form calcium oxide (CaO) and water (H2O).

Calcium oxide reacts with water, generating heat.

#### 10.4 Conditions to avoid

Prevent the accumulation of dust in the environment.

Conditions of moisture during storage may cause lump formation and loss of product quality.

#### 10.5 Incompatible materials

Keep away from water of from damp environments.

The wet concrete is alcalio and incompatible with acids, with ammonium salts, with aluminium and other non-noble metals. In contact with the wet concrete aluminium powder causes the formation of hydrogen. Hydrated lime reacts exothermically with aluminium and with the brass, thus forming hydrogen.

#### 10.6 Hazardous decomposition products

Under normal conditions of storage and use, should be no hazardous decomposition products. Hydrate lime reacts with the carbon dioxide, forming calcium carbonate, a wdespread substance in nature.

### 11 TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects

In the absence of experimental toxicological data on the product itself, the possible health hazards of the product were evaluated based on the properties of the substances containde, according to the criteria laid down by the relevant regulations for the classification.

Therefore, consider the concentration of each hazardous substances possibly mentioned in sect. 3, to assess toxicological effects resulting from exposure to the product.

**ACUTE TOXICITY** 

LC50 (Inhalation - vapors) of the mixture: Not classified (no relevant component)

LC50 (Inhalation - mist/dust) of the mixture: Not classified (no relevant component)

LD50 (Oral) of the mixture: Not classified (no relevant component)

LD50 (Skin) of the mixture: Not classified (no relevant component)

Calcium carbonate

LD50 (Oral) > 6450 mg/kg Rat

Page 6of10

Hydrated lime

LD50 (Oral) > 2000 mg/kg Rat (OECD 425)

LD50 (Skin) > 2500 mg/kg Rabbit (OECD 402)

Cement

LD50 (Skin) > 2000 mg/kg Rabbit

Copolymer of vinyl acetate and ethylene with charge and protective colloid

LD50 (Oral) > 2000 mg/kg Rat

SKIN CORROSION / SKIN IRRITATION

It causes skin irritation

SERIOUS EYE DAMAGE / EYE IRRITATION

t causes serious eye damage

RESPIRATORY OR CUTANAL SENSITIVITY.

Sensitizing to skin.

MUTAGENICITY ON GERMINAL CELLS.

Not responding to the classification criteria for this hazard class.

CARCINOGENICITY.

Not responding to the classification criteria for this hazard class.

TOXICITY FOR REPRODUCTION.

Not responding to the classification criteria for this hazard class.

SPECIFIC TARGET ORGANIC TOXICITY (STOT) - SINGLE EXPOSURE.

May cause irritation to the respiratory tract.

SPECIFIC TARGET ORGAN TOXICITY (STOT) - REPEATED EXPOSURE.

Not responding to the classification criteria for this hazard class.

DANGER IN CASE OF ASPIRATION.

Not responding to the classification criteria for this hazard class.

### 12 ECOLOGICAL INFORMATION

Use this product according to good working practices. nform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

#### 12.1 Toxicity

HYDRATED LIME

LC50 - Fish > 50.6 mg/l/96h Freshwater fish

EC50 - Shellfish > 49.1 mg/l/48h Freshwater invertebrates

EC50 - Algae / Water plants > 184.57 mg/l/72h Freshwater algae

COPOLYMER OF VINYL ACETATE AND ETHYLENE WITH CHARGE AND PROTECTOR COLLOID

LC50 - Fish > 100 mg/l/96h Carp

EC10 - Shellfish > 1000 Purification mud

## 12.2 Persistence and degradability

Dopo l'indurimento il prodotto non presenta rischi di tossicità.

## 12.3 Bioaccumulative potential

Information not available

#### 12.4 Mobility in soil

It may spread during manipulation in the form of powder

#### 12.5 Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%

#### 12.6 Other adverse effects

Information not available

#### 13 DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

Reuse, when possible. Neat product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evalueted according to applicabile regulations. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

#### 14 TRANSPORT INFORMATION

### 14.1 ONU number

Not applicable.

### 14.2 ONU shipping name

Not applicable.

### 14.3 Hazard classes connected to shipping

Not applicable.

### 14.4 Packaging group

Not applicable.

#### 14.5 Environmental hazards

Not applicable.

### 14.6 Special precautions for users

Not applicable.

### 14.7 Shipping of bulk according to MARPOL 73/78 annex and the IBC code

No relevant information.

### 15 REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category None

Restrictions relating to the product or contained substances pursuant to AnnexXVII to EC Regulation 1907/2006 None

Substances in Candidate List (Art. 59 REACH): None

Substances subject to authorisarion (Annex XIV REACH): None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012: None

Substances subject to the Rotterdam Convention: None

Substances subject to the Stockholm Convention: None

Healthcare controls

Workers exposed to this chemical agent to health must undergo health checks according to the provisions of art. 41 of Legislative Decree n. 81 of April 9th 2008, unless the risk for the safety and health of the worker has been assessed irrelevant, according to art. 224 paragraph 2.

#### 15.2 Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

Page 8of10 Bericalce

#### **SAFETY DATA SHEET 120**

# **RASOCOCCIO**

#### 16 OTHER INFORMATIONS

Text of indications of hazard H) mentioned in section 2-3 of the sheet:

Eye Dam. 1

Serious eye damage category 1

Skin Irrit. 2

Skin irritation, category 2

STOT SE Specific target organ toxicity - single exposure, category 3

Skin Sens. 1 Sensibilizzazione cutanea, categoria 1

H318 It causes serious eye damage H315 It causes skin irritation

H335 It may cause respiratory irritation
H317 It may cause allergic skin reaction.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

### GENERAL BIBLIOGRAPHY

- 1. Directive 1999/45/EC and following amendments
- 2. Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EC) 453/2010 of the European Parliament
- 7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
- 8. Regulation (EC) 618/2012 (III Atp. CLP) of the European Parliament
- 9. The Merck Index. 10th Edition
- 10. Handling Chemical Safety
- 11. Niosh Registry of Toxic Effects of Chemical Substances
- 12. INRS Fiche Toxicologique (toxicological sheet)
- 13. Patty Industrial Hygiene and Toxicology
- 14. N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- 15. ECHA website

#### **SAFETY DATA SHEET 120**

# **RASOCOCCIO**

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version.

Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations.

The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### BeriCalce S.r.l.

Via Piave, 23 - 36033 Isola Vicentina (VI) - ITALIA Tel./Fax (+39) 0444 929102 - Tel. (+39) 0444 654919 Skype: bericalce - info@bericalce.com

bericalce.com