



Suitable for external uses.



The product can be pigmented.

RASOCOCCIO

Description of product

RASOCOCCIO is a powdered, medium-to-fine thickness skim coat/decorative finish, characterized by cocchio and marble grits, with excellent workability and resistance to weathering.

The product comes in the characteristic light pink color typical of cocchiopesto, making it suitable for use both as a decorative finish and as an excellent base for any type of finish, including lime-based.

Application Field

Suitable for application to interior and exterior surfaces.

Ideal for leveling walls and plasters, as a general decorative primer, and as a decorative finish.

Product characteristics

RASOCOCCIO is composed of a mix of earthenware powders and grits and fine marble aggregates, mixed together with natural hydraulic lime (NHL) and hydrated lime. The product also consists of special additives designed to ensure excellent wall adhesion, workability and final strength.

RASOCOCCIO has the characteristics of a "mezzanella" mortar, and its thickness can vary between 1 and 10 mm depending on the type of application.

When used as a finish, it is important to keep in mind that the color of the product is given by natural powders, so the latter may vary between different production batches. Eventually the product can be further colored while still maintaining pastel shades.

Technical data	
Name	Rasococcio
Composition	High-quality marble aggregates, mix of earthenware powders and grits, natural hydraulic lime (NHL), hydrated lime, special additives
Aspect	Pink powder
Color	Light pink
Dilution	In water 24-25% by weight
Quantity per layer	Approx. 1.5 kg/sqm for 1 mm thickness
PH	12 (thinned)
Application thickness	1 to 10 mm
Packaging	25 kg buckets
Storage	Store in a dry place with temp. 5° ÷ 30°C
Notice	Temperature for application: min +5°C max +35°C

RASOCOCCIO

Instructions for use

- Preparation of the substrate.
- Remove any parts of the substrate that are not perfectly anchored.
- Remove any oil or grease stains from the surface, operating with a steam jet.
- If necessary, apply 1 coat of primer as a base coat, such as ISOLANTE CONSOLIDANTE ACRILICO or ISOLANTE ANCORANTE BERICO, as needed.
- Mix RASOCOCCIO with the indicated dilution (24-25% by weight) and apply in one or more coats as needed.
- As temperature changes, the product can significantly change drying time.
- Application temperature 5°- 35°C.

Notes

This data sheet was prepared by Bericalce technicians and the data provided constitute the technical and scientific indications tested at the in-house laboratory.

All responsibility, about the results obtained, lies solely with the method and conditions adopted for the application of the product.

These indications constitute valid support in verifying the suitability of the product for the specific case.

Date of issue **22.06.22**

Date of revision 1 **12.02.24**

BeriCalce S.r.l.

Via Piave, 23

36033 Isola Vicentina (VI) - ITALIA

Tel./Fax (+39) 0444 929102

Tel. (+39) 0444 654919

Skype: bericalce

info@bericalce.com

bericalce.com